

Specifications		R-5T
LCD	Size	5.5"
	Resolution	1920×1080 (16:9)
	Pixel Pitch	0.0213(W) x 0.0639(H) mm
	Color Depth	16.7M (True)
	Viewing Angle (Typ.)	160°(H)/160°(V)
	Luminance of white	500 cd/ m <sup>2</sup> (Center)
	Contrast Ratio	1,000 : 1
	Display Area	122.7(H)×69.0(V) mm
Input	1 X HDMI	HDMI Input
	1 X BNC	3G-SDI
	1 X BNC	12G-SDI
	2 X RJ45	RS-422, REMOTE
Output	1 X BNC	12G-SDI (Passive Through Out)
	1 X BNC	3G-SDI (Passive Through Out)
	1 X RJ45	RS-422
Input Signal	12G-SDI	11.88Gb/s
	6G-SDI	5.94Gb/s
	3G-SDI	2.970Gbps
	HD-SDI	1.485Gbps
	SD-SDI	270 Mbps
	HDMI	1080p(60/59.94/50/30/25/24/23.98)/ 1080i(60/59.94/50)/720p(60/50)/480i(60)/480p(60)/576i(50)/576p(50)
SDI Input Signal Formats	SMPTE ST 2082	3840x2160(60/50/59.94p)
	SMPTE ST 2081	3840x2160(30/29.97/25/24/23.98p)
	SMPTE-425M-A/B	1080p(60/59.94/50/30/29.97/25/24/23.98/30sF/29.97sF/25sF/24sF/23.98sF)
	SMPTE-274M	1080i (60/59.94/50)
		1080p (30/29.97/25/24/24sF/23.98/23.98sF)
	SMPTE-296M	720p(60/59.94.50/30/29.97/25/24/23.98)
	SMPTE-125M	480i (59.94)
ITU-R BT.656	576i (50)	
Audio In	Embedded Audio	
Audio Out	Speaker	
Power	DC 12V / 2.9A	
Power Consumption (Approx.)	35W	
Operating Temperature	0°C to 45°C (32°F to 113°F)	
Storage Temperature	-20°C to 60°C (-4°F to 140°F)	
Main Body Dimensions (mm/inch)	439 X 87.5 X 118.7 (17.28 X 3.44 X 4.67)	
Main Body Dimensions with RMK (mm/inch)	480.2 X 87.5 X 141.7 (18.9 X 3.44 X 5.58)	
Box Dimensions (mm/inch)	555 X 180 X 250 (21.85 X 7.08 X 9.84)	
Weight	2.9Kg/6.4lbs	
Basic Accessories	DC Power adapter, Rack Mountable Kit	
Optional Accessories	-	

\* The specification above may be changed without notice.

\* When using a DC Adapter other than the one supplied by the manufacturer, please be advised that the adapter with DC 12V/3A ~ 6A can be compatible with the monitor.