

Specifications		F-7HS
LCD	Size	7"
	Resolution	1920×1200 (16:10)
	Pixel Pitch	0.07875(H) X 0.07875(V) mm
	Color Depth	1.073B Colors (10 bit)
	Viewing Angle	160°(H) / 160°(V)
	Luminance of white	1800 nits(Max)
	Contrast Ratio	1200 : 1
	Display Area	151.2(H) X 94.5(V) mm
Input	1 X HDMI	HDMI Input
	1 X BNC	3G/HD/SD SDI Input
Output	1 X HDMI	HDMI Output (HDMI loop out, SDI-to-HDMI Conversion output)
	1 X BNC	3G/HD/SD SDI Output (SDI loop out, HDMI-to-SDI Conversion output)
Input Signal	3G-SDI	2.970 Gb/s
	HD-SDI	1.485 Gb/s
	SD-SDI	270 Mb/s
	HDMI	480i / 480p / 576i / 576p / 720p / 1080i / 1080p
SDI Input Signal Formats	SMPTE ST-425M-A/B	1080p (60/59.94/50/30/29.97/25/24/23.98/30sF/29.97sF/25sF/24sF/23.98sF)
		1080i (60/59.94/50)
	SMPTE ST-274M	1080i (60/59.94/50)
		1080p (30/29.97/25/24/24sF/23.98/23.98sF)
	SMPTE ST-296M	720p (60/59.94/50)
	SMPTE ST-125M	480i (59.94)
ITU-R BT.656	576i (50)	
Update	1 x USB	USB A type, Firmware Upgrade
Audio In	SDI Embedded Audio (Group, Ch Selectable)	
Audio Out	External Output Port (3.5m Phone Jack)	
Power	DC 6V ~ 34V	
Power Consumption (Approx.)	21W(Max)	
Operating Temperature	0°C to 40°C (32°F to 104°F)	
Storage Temperature	-20°C to 60°C (-4°F to 140°F)	
Dimensions	Main Body	211 x 125 x 28.3mm (8.3 x 4.95 x 1.11 inch)
	Shipping Box	290 X 158 X 83mm (11.42 X 6.22 X 3.27 inch)
Weight	0.76kg / 1.67lbs	
Basic Accessories	D-Tap-C Cable, Camera Mount	
Optional Accessories	External Acrylic Protector, Sun Hood, D-Tap Power Cable, Battery Bracket, V-Mount Battery Bracket, Anton-Bauer(Gold) Battery Bracket, Carrying Case, DC Adapter, HDMI Bracket	

\* The specification above may be changed without notice.