

Specifications		LVM-180A
LCD	Size	18.5"
	Resolution	1920 x 1080 (16:9)
	Pixel Pitch	213(per one triad) x 213 [um]
	Support Color	16.7M colors (True 8 Bit) / 10bit Video Signal Processing
	Luminance of white	500cd/m2 (Typical)
	Contrast Ratio	1000:1 (Typical)
	Active Area	408.96(H) x 230.04 (V) [mm]
Input Connector	2 x BNC	SDI Channel Input
	1 x BNC	CVBS Input
	1 x HDMI	HDMI Input
	1 x DVI-I	DVI Input
Output	1 x BNC	SDI Channel (Active Through Out)
	1 x BNC	CVBS Output
Input Signal	3G-SDI	2.970Gbps
	HD-SDI	1.485Gbps
	SD-SDI	270 Mbps
	Analog	Composite
	DVI	VESA/IBM Modes
	HDMI	480i / 480p / 720p / 1080i VESA/IBM Modes
Analog Input Spec	Composite	1.0Vpp (with Sync)
SDI Input Signal Formats	SMPTE-425M-A/B	1080p(60/59.94/50/30/29.97/25/24/23.98/30sF/29.97sF/25sF/24sF/23.98sF)
		1080i(60/59.94/50)
	SMPTE-274M	1080i (60/59.94/50)
		1080p (30/29.97/25/24/24sF/23.98/23.98sF)
	SMPTE-296M	720p (60/59.94/50)
	SMPTE-260M	1035i (60/59.94)
	SMPTE-125M	480i (59.94)
ITU-R BT.656	576i (50)	
Audio	Audio In	Embedded Audio / Analog Stereo (Phone Jack)
	Audio Out	Analog Stereo (Phone Jack), Internal Speaker (Stereo)
Power	AC100~240V(50~60Hz) / DC 12V	
Power Consumption (Approx.)	30 Watts	
Operating Temperature	0°C to 40°C (32°F to 104°F)	
Storage Temperature	-20°C to 60°C (-4°F to 140°F)	
Dimensions	Main Body (mm/inch)	442.5 x 309.2 x 65.4 (mm) / 17.42 x 12.17 x 2.57 (inch)
	Main Body with stand (mm/inch)	483.5 x 332.9 x 137.5 (mm) / 19.03 x 13.1 x 5.41 (inch)
Weight	5.6 kg / 12.34 lbs	
Accessory	Basic	AC Power Cord, Stand
	Optional	Sun Hood, Acrylic Filter, Rack Mount Kit, Carrying Case, V-Mount, G-Mount

\*The specifications above may be changed without notice.