

Specifications		LVM-328W	
LCD	Size	31.5"	
	Resolution	1920 X 1080 (16:9)	
	Pixel Pitch	0.121(H) X 0.363(V) mm	
	Color Depth	8bit, 16,777,216 Colors	
	Viewing Angle	H: 178degrees / V: 178degrees	
	Luminance of white	400 cd/ m <sup>2</sup>	
	Contrast Ratio	1200 : 1	
	Display Area	698.40(H) X 392.85(V) mm	
Input Connector	1 X DVI-I	DVI-I(RGB) IN	
	3 X BNC	Analog Input	
	2 X BNC	SDI A/B Channel Input	
	1 X HDMI	HDMI Input	
Output	3 X BNC	Analog Output	
	2 X BNC	SDI A/B Channel (Loop Through Out)	
	1 X BNC	EXT SYNC OUT(Active Through Out)	
Input Signal	Analog	Composite/ S-Video / Component Video / RGB	
	3G-SDI	2.970Gbps	
	HD-SDI	1.485Gbps	
	SD-SDI	270 Mbps	
	DVI	VESA/IBM Modes	
	HDMI	480i / 480p / 720p / 576i / 576p / 1080i / 1080p & VESA / IBM Modes	
Analog Input Spec	Composite	1.0Vpp (with Sync)	
	S-Video	1.0Vpp (Y with Sync), 0.286Vpp(C)	
	Component	1.0Vpp (Y with Sync), 0.7Vpp (Pb,Pr)	
	RGB	1.0Vpp (Y with Sync), 0.7Vpp (Pb,Pr)	
SDI Input Signal Formats	SMPTE-425M-A/B	1080p (60/59.94/50/30/29.97/25/24/23.98/30sF/29.97sF/25sF/24sF/23.98sF) 1080i (60/59.94/50)	
		SMPTE-372M	Dual HD-SDI YPbPr (4:2:2)
	Dual HD-SDI YPbPr RGB (4:4:4)		1080p(50/59.94/60)
			1080p/psf(30/29.97/25/24/23.98)
	SMPTE-274M	1080i (60/59.94/50)	
		1080p (30/29.97/25/24/24sF/23.98/23.98sF)	
	SMPTE-296M	720p (60/59.94/50)	
	SMPTE-260M	1035i (60/59.94)	
	SMPTE-125M	480i (59.94)	
	ITU-R BT.656	576i (50)	
2K Format	2048 x 1080(23.98p/psf, 24p/psf)		
Audio In	Embedded Audio / Analog Stereo (Phone Jack)		
Audio Out	Analog Stereo (Phone Jack)		
Power	AC100~240V(50~60Hz)		
Power Consumption (Approx.)	145 Watts(Max.)		
Operating Temperature	0°C to 35°C (32°F to 95°F)		
Storage Temperature	-20°C to 60°C (-4°F to 140°F)		
Main Body Dimensions (mm/inch)	769.4 x 485.1 x 102.1 (30.29 x 19.1 x 4.01)		
Main Body Dimensions with stand (mm/inch)	769.4 x 539.3 x 255 (30.29 x 21.23 x 10)		
Box Dimensions (mm/inch)	920 X 675 X 350 (36.22 X 26.57 X 13.78)		
Weight	22.25Kg / 49.05 lbs		
Basic Accessories	AC Power Cord, Stand, Manual		
Optional Accessories	Carrying Case		

\* The specification above may be changed without notice.